



Omschrijving	Waarde						
Artikelcode	T8-03-1212	T8-03-1218	T8-03-1220	T8-03-1520	T8-03-1522	T8-03-1525	T8-03-1530
Lengte TL in mm	1200	1200	1200	1500	1500	1500	1500
Verbruik LED	12 Watt	18 Watt	20 Watt	20 Watt	22 Watt	25 Watt	30 Watt
Vervangt TL van	36 Watt	36 Watt	36 Watt	58 Watt	58 Watt	58 Watt	58 Watt
Lichtstroom lumen ca	2415 lm	3622 lm	4025 lm	4025 lm	4427 lm	5031 lm	6037 lm
Lichtopbrengst in lumen ca	2100 lm	3150 lm	3500 lm	3500 lm	3850 lm	4375 lm	5250 lm
Branduren	> 50.000 uur						
Power factor	> 0,90						
Operating Voltage	100-240VAC						
Frequency	50 Hz						
Type LED	SMD 2835						
Stralingshoek	120°, 140°						
Lichtkleur	3000K, 4000K, 6000K						
IP waarde	IP20						
Cover	Melkglas (M) / Transparant (T)						
Toepassing	Kantoor, gang, school, garage, werkplaats etc.						
Productgarantie	5 jaar						
Certificaten	CE, ROHS, SAA, TÜV						
Opties	Flicker Free						