



Omschrijving	Waarde			
Artikelcode	DNDRH-01-25W	DNDRH-01-30W	DNDRH-01-40W	DNDRH-01-60W
Afmeting in mm	L243*B150*H90	L243*B150*H90	L243*B150*H90	L243*B150*H90
Gatmaat in mm	L230*B130	L230*B130	L230*B130	L230*B130
Verbruik LED	25 watt	30 watt	40 watt	60 watt
Vervangt halogeen	65 watt	75 watt	100 watt	125 watt
Lichtstroom lumen ca	2875 lm	3450 lm	4600 lm	6900 lm
Lichtopbrengst in lumen ca	2500 lm	3000 lm	4000 lm	6000 lm
Branduren	> 50.000 uur			
Power factor	> 0,95			
Color Rendering Index	Ra> 80			
Operating Voltage	AC200-240V			
Frequency	50/60 Hz			
Type LED	COB			
Stralingshoek	120°			
Lichtkleur	3000K / 4000K / 6000K			
IP waarde	IP22			
IK waarde	IK04			
Cover	Transparant (T), Melkglas (M)			
Toepassing	Winkel, showroom, kerk			
Productgarantie	3 jaar			
Certificaten	CE, ROHS, TÜV, SAA			
Opties	Kantelbaar			